

EL-WiFi-TP

WiFi Temperature Probe Data Logging Sensor




Z.I. Le Trési 6 D - 1028 Prévèrenge
Tél 021 637 12 37 - Fax 021 637 12 38
www.thermolab.ch
info@thermolab.ch

WiFi Temperature
Probe Data Logging
Sensor

EL-WiFi-TP

FEATURES

- Temperature data logging sensor with thermister probe
- WiFi capability and integrated display
- Wireless connectivity to PC via WiFi
- Easy sensor set-up using free PC software
- View and analyse multiple sensors using the PC application, including immediate graphing of historic data
- Measurement range -40 to +125 °C (-40 to +257 °F)
- 802.11b compliant
- Capable of logging greater than 1 million data entries
- Sensor memory stores all data even if WiFi is temporarily disconnected
- Main unit IP55, probe IP67
- Rechargeable internal lithium polymer battery
- Configurable high and low alarms with indicator
- Max & Min readings
- Low battery indicator
- WiFi connection indicator
- USB port used for recharging
- Supplied with removable thermister probe, micro USB lead & wall bracket



The EL-WiFi-TP sensor measures the temperature of the environment in which the probe is situated. Data is transmitted wirelessly via a WiFi network to a PC and viewed using free software available to download from the Lascar Electronics website. During configuration the sensor will search for an existing wireless network whilst physically connected to the PC. It can then be placed anywhere within range of the network. If the sensor temporarily loses connectivity with the network, it will log readings until it is able to communicate again with the PC application (max 120 days at 10 second sample interval). The range of the sensor can be increased by using WiFi extenders.

The probe can be used in a wide range of temperature situations e.g. manufacturing processes, cold storage and hot storage.

This EL-WiFi-TP is a low powered battery device. When configured using typical transmission periods (e.g. once every 5 minutes) the sensor will operate for over one year. The battery can then be recharged via a PC or USB +5V wall adapter using the USB lead provided.

The software installed on the PC will allow set-up, data logging and data review. Set-up features will include sensor name, °C/°F, sample rate, and high/low alarms. Once configured, historic data can be viewed via the graphing tool or exported to Excel.

EL-WiFi-TP

WiFi Temperature Probe Data Logging Sensor

This sensor stands alone by itself on a horizontal surface and comes with a wall bracket that can be screwed onto a wall or flat surface. The sensor clips into the bracket.

The sensor is supplied with a thermistor probe with an attachment so that the probe can be securely fixed to flat surfaces.

The probe is removable so alternative probes can also be used to meet specific requirements providing they operate within the same temperature range.

Specifications	Minimum	Typical	Maximum	Unit
Battery life		>1*		Year
USB supply voltage	4.5v		5.5v	V d.c.
Probe temperature measurement range	-40 (-40)		+125 (+257)	°C (°F)
Internal resolution		+/- 0.1		°C
Probe temperature accuracy (overall error)		+/- 0.5	+/- 2.0	°C
Probe clip operating temperature range	-40 (-40)		+100 (212)	°C (°F)
Logging rate (user configurable)	Every 10s	30 seconds	Every 12hrs	Transmission rate
Unit operating temperature range	-20 (-4)		+60 (+140)	°C (°F)

* Typical but could be less if frequent transmissions

Warning - do not exceed operating temperatures

PHYSICAL DIMENSIONS

All dimensions in millimetres (mm)

