








PT100 Class A Temperature Probes

for use with the Precision 0.1 °C thermometer

		order code	
<p>penetration probe</p>  <p>Ø3.3 x 130 mm</p>	<p>This stainless steel penetration probe is strong and versatile, ideal for measuring liquids and semi-solids accurately in a variety of applications. Response time less than four seconds. Probe temperature range -50 to 200 °C.</p>	160-160	
<p>air or gas probe</p>  <p>Ø4.5 x 130 mm</p>	<p>This stainless steel air or gas probe is ideal for measuring air or gas temperatures accurately in rooms and ducts in HVAC and industrial applications. Response time less than four seconds. Probe temperature range -50 to 200 °C.</p>	160-300	
<p>between pack probe</p>  <p>Ø6 x 130 mm</p>	<p>This heavy duty, stainless steel, between pack probe is strong and versatile, designed to accurately measure between packets/boxes of produce. Response time less than 14 seconds. Probe temperature range -50 to 200 °C.</p>	160-060	
<p>liquid probe</p>  <p>Ø3.3 x 130 mm</p>	<p>This liquid probe features a rigid, stainless steel stem with a flat tip. The probe is suitable for accurate temperature measurement in a wide variety of laboratory applications. Response time less than four seconds. Probe temperature range -50 to 200 °C.</p>	160-220	
<p>air or gas wire probe</p>  <p>Ø3.7 x 30 mm with 1000 mm FEP lead</p>	<p>This FEP insulated air or gas wire probe is ideal for measuring air or gas temperatures accurately in a variety of HVAC and industrial applications. Response time less than four seconds. Probe temperature range -50 to 200 °C.</p>	160-372	

PT100 1/10 DIN Temperature Probes

for use with the Precision Plus 0.01 °C thermometer

		order code	
<p>liquid probe</p>  <p>Ø3.3 x 130 mm</p>	<p>This hand held liquid probe features a rigid, stainless steel stem with a flat tip. The probe is suitable for high accuracy temperature measurement in a wide variety of laboratory applications. Response time less than four seconds. Probe temperature range -200 to 200 °C.</p>	160-222	
<p>liquid probe</p>  <p>Ø4.8 x 250 mm with 2 m PTFE lead</p>	<p>This liquid probe features a rigid, stainless steel stem with a flat tip. The probe is suitable for high accuracy temperature measurement in a wide variety of laboratory applications. Response time less than ten seconds. Probe temperature range -200 to 200 °C.</p>	160-446	

